

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)


PCT

(10) International Publication Number
WO 2005/053174 A1

- (51) International Patent Classification⁷: **H04B 1/40**, 7/155, H04L 27/18
- (21) International Application Number: PCT/GB2004/004910
- (22) International Filing Date: 19 November 2004 (19.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0327041.0 21 November 2003 (21.11.2003) GB
- (74) Agents: MACKETT, Margaret, Dawn et al.; BAE SYSTEMS plc, Group IP Department, Lancaster House, P.O. Box 87, Farnborough Aerospace Centre, Farnborough Hampshire GU14 6YU (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (for all designated States except US): BAE SYSTEMS PLC [GB/GB]; 6 Carlton Gardens, London Greater London SW1Y 5AD (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): RICHARDSON, Michael, Richard [GB/GB]; 16 Knyght Close, Romsey Hampshire SO51 5UX (GB).

[Continued on next page]

(54) Title: SIGNAL REGENERATION



(57) Abstract: Described herein is a method for signal regeneration, particularly, of the signal type transmitted by cellular base stations used in cellular telephone network systems. It is sometimes necessary to regenerate an accurate replica of a transmitted signal, by removing any errors that are present and/or compensate for any degradation that occur during transmission. The signal structure of signals transmitted within the cellular network systems is of a known form with predefined characteristics such as synchronisation signals, error correction bursts or training sequences. The method includes determining frame timing of the received signal, identifying the locations of sequences within the signal from the frame timing, identifying the structure of the sequences, estimating phase shift values at the locations of the sequences, demodulating the symbol stream using the estimated phase shift values and the values to regenerate the signal that is substantially identical to the one that would have been received directly from the transmitter over a high quality land-line.



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.